



The alternative to CIJ printers

T127P TIJ printer with HP 2.5 Technology



Inkjet Coding Components,SI (ICC Group)
Pol Ind Cantabria C/Majuelo, nº 5
26009 Logroño (La Rioja) SPAIN

Phone: +34 941 26 50 66
info@tidirefi.com
www.tidirefi.com

Inkjet Technology by HP





T127P

INKJET THERMAL PRINTER

TECHNICAL

SPECIFICATIONS

Printing by HP45 ink cartridge (Hewlett Packard TIJ2.5 inkjet Technology)

Dimensions (LxWxH): 107.5 x 74.5 x 83 mm

Weight: 450g (without the cartridge)

Screen: Automatic rotation 2.8" 256K colours TFT LCD display

PSU: AC 100V-240V, 50/60Hz, 1.4A. Maximum consumption: 48W

Anti-shock assembly mechanism

Printing distance up to 6 mm

STANDARD CHARACTERISTICS

Bluetooth with connection via Smartphone and tablet, using Android device

Autonomous functioning with direct connection by USB keyboard, no PC required

PC connectivity for several applications

AUX I / O port for external sensor, encoder and alarm kit connection

USB2.0 Flash for firmware, several colours adjustable internal sensor

Automatic data backup system

Automatic cleaning of the cartridge

Storing up to 100 messages inside the printing memory

Password protection

Automatic check up of the ink cartridge (water or make up) varying automatically the printer parameters

New compartment cartridge holder, easier to remove

Hot-swap: Circuit protection for a fast change of the cartridge

Real time report for Android e iOS device

PRINTING AND SPEED

Languages menu: Spanish (by default) and multiple languages

High of the message up to 6 lines of 1,69 to 1 line of 12,7 mm

Characters of maximum input up to 150 per line

Maximum length of the stencil up to 500mm

Type of information to print: alphanumeric codes, logos, date / time, expiration date, Julian date, shift code, meter, bar codes, variable data base and multiple fonts.

Resolution: Max 600X600dpi

Printing speed: max. 228m / min @ 300x100 dpi

Up to 5 levels of optical density for saving ink

Displaying of messages to print and the amount of ink remained in the cartridge

INKS

Water-based and make up for all types of substrates

OPERATION

Working temperature between 5 and 50°C

TEMPERATURE

WARRANTY

24 months

